



TransAir™ STS-1020

Intelligent Cloud-Enabled Mobile Gateway

- Dual LTE-A with GPS
- Enterprise-grade Wi-Fi Access Point
- Compute and storage to host applications
- Vehicle interfaces to connect vehicular network to cloud
- Sensors to enable IOT applications



SKU

STS-1020

STS-1020-A

DESCRIPTION

Multi-service Mobile Gateway with 2 LTE-A (North America and Europe), 2 Wi-Fi (802.11a/b/g/n/ac), PoE+ and Application Engine

Multi-service Mobile Gateway with 2 LTE-A (APAC), 2 Wi-Fi (802.11a/b/g/n/ac), PoE+ and Application Engine

The LILEE Systems TransAir™ STS-1020 is an enterprise-class vehicle communications gateway that provides Internet connectivity to onboard applications. The STS-1020 provides wired and wireless connectivity to onboard devices, vehicle to ground, and ground to the back office. The built-in Wi-Fi Access Point provides dual band (2.4/5 GHz) 802.11ac connectivity and Power over Ethernet (PoE). In addition, it has Gigabit Ethernet (GbE) ports to provide wired connectivity to both passenger and operational devices.

LileeOS, software running on STS, provides Layer 2 functionality, security, Quality of Service (QoS), traffic segmentation and management, application isolation and link aggregation. The dynamic weighted load balancing (DWLB) aggregates bandwidth simultaneously across LTE,

Wi-Fi, and Ethernet, allowing the highest amount of throughput at the lowest possible cost – ideal for running multiple onboard applications that demand high-throughput and reliable connectivity.

LILEE Systems T-Cloud, the simple, intuitive, flow-based and cloud-based management, provides monitoring, onboarding, and configuration of onboard devices, connectivity, and edge and cloud applications. A wide range of interface options combined with the flexibility to run applications directly on the STS accelerates custom application development. The open cloud platform enables easy integration of third-party cloud applications, such as CAD/AVL, e-log (electronic logging), and onboard entertainment.

STS-1020 Specifications

Processor / Memory / Storage

Intel Atom X-series Quad-Core Processor
4 GB on board memory
2 x SATA SSD 2.5" disk bays (32 GB included in SATA0)

LTE Interfaces

2 x LTE CAT 6 (LTE-A) to support up to 300 Mbps each
4 x SIM card slots
4 x LTE 4G antenna connectors (2 per LTE 2 x 2 MIMO)
LTE Band Support in North America and Europe -
B1,B2,B3,B4,B5,B7,B8,B12,B13,B20,B25,B26,B29,B30,B41
LTE Band Support in APAC -
B1,B3,B5,B7,B8,B18,B19,B21,B28,B38,B39,B40,B41
Advanced Satellite System support -
GPS (US), Glonass (Russia), Beidou (China), Galileo (EU)
1 x GPS antenna connector

Wi-Fi Interfaces

2 x 802.11 ac/a/n (5 GHz) b/g/n (2.4 GHz) interfaces support up to 1.3 Gbps
6 x WLAN antenna connectors (3 x 3 MIMO)
Support for up to 128 clients per radio
Up to 8 SSIDs per radio
Dual radio mode (AP or client)
Automatic or manual channels selection

Onboard Sensors

3-axis gyroscope and 3-axis accelerometer

Physical Interfaces

1 x HDMI connector (audio and video)
1 x DB15 connector to provide OBD-II (for small vehicles) and J1939 (for buses)
1 x Digital I/O connector (1 true ignition digital input, 3 digital-in, 2 digital-out, 6 GND)
1 x USB 2.0
1 x USB 3.0
6 x 10/100/1000 Mbps Ethernet ports – 4 of the ports PoE 802.3at Type 2
2 x RS-232/422/485 Serial port via DB-9
1 x Maintenance port (RJ45) for dedicated diagnostic connection
1 x Serial console port via RJ45
1 x Reset button
LED indicators: PWR, RDY, ALM, GPS, POE, LTE0, LTE1, WLAN0, WLAN1, AUX0, AUX1

Protocol Support

IP Routing, DHCP, SNMPv2, SMS (Short Message Service), NTP, NAT
QoS Priority queuing, classification, and marking
8 VLAN/TOS based queues for application prioritization
NAT (dNAT & sNAT)
IPSec Protocol
PPPoE
Link aggregation across LTE (different providers), Wi-Fi, and Ethernet

Security

IPsec, SSH, DTLS
Encryption: TKIP, AES/CCMP
Authentication
- 802.1X/EAP for WPA/WPA2 Enterprise
- PSK for WPA/WPA2 Personal
- On-device RADIUS Server
Firewall with port forwarding and filtering
Captive Web Portal
Content Filtering

Remote Management

Virtual IP KVM remote management
Centralized Management
- Cloud-based network, device, and client monitoring
- Guided network configuration
LILEE Mobility Controller (LMC) RESTful APIs, WebSocket APIs, and SNMP
(host and interface MIBs) for commercial network management integration

Local Management

Serial console port
Ethernet maintenance port (CLI via SSH)

Physical Characteristics

Cooling design	Fanless
Housing	Metal housing
Dimensions (H x W x L)	2.6 x 7.1 x 11.7 in (67 x 181 x 298 mm)
Weight	6.61 lb. (3 kg)
Installation	Shelf and wall

Environmental Limits

Functional Operating Temperature	-40 to 70 °C (-40 to 158 °F)
Storage Temperature	-55 to 85 °C (-67 to 185 °F)
Ambient Relative Humidity	5% to 95% (non-condensing)

Power

Input Voltage	10 to 30 VDC
Power Connector	4-pin terminal block header, male pin
Power Consumption	4.8 W Minimum (soft off)
	15 W No external connections (idle)
	95 W Maximum with PoE

Certifications

STS-1020	FCC, PTCRB, CE, EN 50155
STS-1020-A	CE, CB, EN 50155

For more information, contact your sales representative or email sales@lileesystems.com.

LILEE Systems
641 River Oaks Parkway
San Jose, CA 95134
+1 (408) 988-8672
www.lileesystems.com

REV 2018.03.08