



TransAir™ STS-2025

Rugged Intelligent Cloud-Enabled Mobile Gateway

- AAR S9401 standard compliant for operations in extreme environments
- Dynamic load balancing and link aggregation for fast, reliable WAN connectivity
- Software configurable dual Wi-Fi AP for high-bandwidth applications
- Application containers running multiple independent applications
- Centralized cloud-based monitoring and management



The LILEE Systems TransAir™ STS-2025 is a ruggedized, intelligent cloud-enabled mobile gateway that delivers wireless connectivity and enables transportation operators to run operational and passenger applications.

STS-2025 comes with two 5G/LTE Cat. 20 WWAN interfaces, designed for aggregation and dynamic load balancing for fast and reliable WAN connectivity. The built-in Wi-Fi Access Point provides dual-band 802.11 ax/ac/a/n (5GHz) and 802.11 b/g/n (2.4GHz) connectivity and Power over Ethernet (PoE). It also supports FirstNet band 14 and band 48 CBRS Private LTE for secure, highly reliability, low latency communication.

AAR S9401 standards compliance and IP54 rating allows STS-2025 to operate in extreme environments and makes it suitable for onboard locomotives, hi-rail vehicles and remote wayside locations.

STS-2025 is a cloud-enabled platform that supports centralized monitoring and management of devices and applications. Remote deployment, zero-touch onboarding, group configurations and troubleshooting help organizations increase operational efficiency, reduce operating cost and optimize device uptime.

SKU

STS-2025

Description

Rugged Intelligent Mobile Gateway with 2 5G/LTE, 2 Wi-Fi (802.11 ax/ac/a/b/g/n), PoE+ and Application Containers

STS-2025 Specifications

Processor / Memory / Storage

Intel Atom Quad-Core Processor with IOMMU
8 GB onboard memory
2 * mSATA slots (32GB SSD preinstalled at SATA0)

Cellular Interfaces

5G: sub-6 FDD and TDD, SA and NSA operations, up to 5.5 DL/1.5 UL Gbps
4G: 7 CA, up to 20 layers DL/2 CA UL, 256-QAM DL/UL, up to 2 Gbps DL/211 Mbps UL
4 * SIM slot (2 * 4FF/Nano SIM slots for each LTE)
8 * SMA connector (4 x 4 MIMO for each LTE)
4 x 4 MIMO support on RF bands:
- 5G: n1, n2, n3, n7, n25, n38, n40, n41, n48, n66, n77, n78, n79
- 4G: B1, B2, B3, B4, B7, B25, B30, B66, B38, B39, B40, B41, B42, B43, B48, B46

Wi-Fi Interfaces

Current dual-band 802.11 ax/ac/a/n (5GHz) and 802.11 b/g/n (2.4GHz) operations support up to 1.2 Gbps
2 x WLAN antenna connectors (2 x 2 MIMO)
Support for up to 128 clients per radio
Up to 8 SSIDs per radio
Dual radio mode (AP or client)
Automatic or manual channels selection

Bluetooth Interfaces

Bluetooth V5.2, V5.1, V5.0, V4.2, V4.1, V4.0LE, V3.0, V2.1+EDR

Onboard Sensors

GNSS (GPS, GLONASS) receiver with dead reckoning
3-axis gyro
3-axis accelerometer
2 * CAN 2.0b bus

Physical Interfaces

1 * Power connector (M12 4+1PE K-Coded)
1 * HDMI (Circular connector)
1 * USB 3.0 (Circular connector)
1 * USB 2.0 (Circular connector)
8 * LTE antenna (SMA)
1 * Wheel tick input (SMA)
1 * GPS antenna (SMA)
4 * SIM slots (4FF/Nano SIM)
2 * WiFi/BT antenna (RP-SMA)
1 * Maintenance port and Serial console (M12 12-pin A-Coded)
2 * RS-232/422/485 (M12 8-pin A-Coded)
1 * Digital Input connector (4 * digital input, 4 * ground, M12 8-pin A-Coded)
1 * Digital Output connector (4 * digital output, 4 * ground, M12 8-pin A-Coded)
1 * CAN bus connector (2 * CAN-H/-L pairs, M12 8-pin A-Coded)
4 * 10/100/1000 Ethernet M12 X-Coded ports with 802.3at Type 2 support

Protocol Support

IP Routing, DHCP, SNMPv2, SMS (Short Message Service), NTP, NAT
QoS Priority queuing, classification, and marking
8 VLAN/TOS based queues for application prioritization
NAT (dNAT & sNAT)
IPSec Protocol
PPPoE
Link aggregation across LTE (different providers), Wi-Fi, and Ethernet

Security

IPsec, DTLS, SSL
Encryption: TKIP, AES/CCMP
Authentication
- 802.1X/EAP for WPA/WPA2 Enterprise
- PSK for WPA/WPA2 Personal
- RADIUS Server
Port forwarding and filtering
Captive Web Portal
Content Filtering

Remote Management

Centralized Management
- Cloud-based network, device, and client monitoring
- Network configuration

Local Management

Serial console port
Ethernet maintenance port

Physical Characteristics

Cooling design	Fanless
Housing	Metal
Dimensions (H x W x L)	2.4 x 7.1 x 11.6 in (60 x 180 x 294 mm)
Weight	7.72 lbs. (3.5 kg), estimated
Installation	Shelf and wall

Environmental Limits

Functional Operating Temperature	-40 to 70 °C (-40 to 158 °F)
Storage Temperature	-55 to 85 °C (-67 to 185 °F)
Ambient Relative Humidity	5% to 95% (non-condensing)

Power

Input voltage: 10 – 30 VDC
Shutdown threshold voltage: 9 VDC
Consumption:
- 200mW during soft off
- 12W at idle, no external connections
- 150W maximum with PoE (90W maximum to devices)

Certifications

FCC, PTCRB, CE, CB, EN 50155, EN 45545, AAR S9401, IP54

LILEE Systems

91 East Tasman Drive, Suite 150
San Jose, CA 95134
United States
www.lileesystems.com

